

ASD Z-DRIVE TUG

Commercial and Operational Office P.O. Box 930001 Empire Heights Building Suite 13F-A-01, Business Bay Dubai, United Arab Emirates Tel: + 971(4) 551 9930 Fax: +971(4) 551 9931 info@vortexoffshore.com | www.vortexoffshore.com

5364 BHP | 70 TBP



- SPECIFICATIONS:

GENERAL:

Vessel Type: Flag: Port of Registry: Classification: Notation: Azimuth Stern Drive TUVALU FUNAFUTI Lloyd's Register +A1 (E) AMS Towing vessel, FiFi vessel class 1

DIMENSIONS:

Length Overall:	
Beam:	
Depth:	
Design Draft:	
GRT:	
Displacement:	

31.00 m Moulded 11.00 m Moulded 5.60 m 4.30 m 471 T 820.45 T

CAPACITIES:

Fuel Oil: Fresh Water:

ASD - Terminal & Towage Support, FIFI 1

MACHINERY:

Main Engines: Total Power: Z-Propeller: Bow Thruster: 2 x CAT 3516C, 2 x 2682BHP at 1600rpm 2 x Rolls-Royce US255 P30FP, Ø2600mm 1x Tunnel Bow thruster c/w Cummins Diesel Engine (175kW)

POWER GENERATION:

Main Generators:2 x CAT C6.6, 125kW/50Hz/1500rpmHarbour Generator:1 x CAT C4.4 51kW/50Hz/1500rpm

ACCOMMODATION:

2 x 1 Berth Cabins	(2 men)
2 x 3 Berth	(6 men)
4 x 1 berth	(4 men)
Total Berths:	12 Men

PERFORMANCE:

Bollard Pull:	70 T (Ahead)
	65 T (Stern)
Speed:	12.5 Knots

The Vessel specifications are reviewed and new brochures printed at regular intervals. Every endeavour has been made to provide accurate information on this brochure; however, the vessel owners do not accept any liability for errors, omissions or misprints published.

170 T

34 T



ASD Z-DRIVE TUG VORTEX VEGA

DECK EQUIPMENT:

Anchor:	2 x HHP anchors, each 675kg
Towing Hook:	SWL 70Tonnes
Anchor Winch:	1 x W-rig split single drum winch,
Drum capacity:	110m+110m of dia 80mm pp rope
Aft Towing Winch:	1 x W-rig single drum winch,
Drum capacity:	700m x52mm
Deck Crane:	1 x EFFER Marine Crane, 1 ton @ 9m

VESSEL SAFETY EQUIPMENT:

Inflatable Liferafts: Lifebouys:	3 x 12 men 8
Fireman's outfits:	6
Life Jacket:	16
WorkVest:	1 shipset
Pyrotechnics:	1 shipset
Fire Extinguisher:	1 shipset
Fire Alarm Panel:	1 shipset
CO2 System:	1 shipset

EXTERNAL FIRE FIGHTING:

Equipment:

Classed as FiFi1 FFS, one 2700 m3/h driven by port main engine

Commercial and Operational Office P.O. Box 930001 Empire Heights Building Suite 13F-A-01, Business Bay

Dubai, United Arab Emirates Tel: + 971(4) 551 9930 Fax: +971(4) 551 9931 info@vortexoffshore.com | www.vortexoffshore.com

5364 BHP | 70 TBP

NAVIGATION/ COMMUNICATION:

GMDSS: VHF: 2 Way Portable VHF: SART: MF/ HF: FPIRB: NAVTEX: INMARSAT C: Radar (No.1): Radar (No.2): BNWAS: GPS: Depth Sounder: Auto Pilot: AIS: Magnetic Reflector Compass: 1 x SAURA SR-165 GPS Compass: Sound Systems: Search Light: Flood Light:

A1+A2+A3 Area 2 x JRC JHC-770S 3x JRC JHS-7 1 x JOTRON Tronsart 20 1 x JRC JSS-2150 1 x JOTRON TRON 60S 1 x JRC NCR-333 1 x JRC JUE-87 1 x JRC JMA-5212-6 1 x JRC JMA-2353 (Non IMO) 1 x A006.6 1 x JRC JLR-7500 1 x JRC JFE-380 1 x SAURA SA-10 1 x JRC JHS-183 1 x VECTOR G2 Sound Power Phones and PA System 2 x Francis (2000W) 4 x Francis (2 x 500W, 2 x 1000W)

MISCELLANEOUS:

Oily Water Separator: 1 No, 0.5m³/hr with 15ppm Sewage Treatment Plant: suit for 12men Fresh Water Heater: 1501 Fuel Oil Purifier: 1 No, MAB103 Air Compressor: 2 Nos, 20m³/h @30bar Air Receiver: 2 Nos, 100L@30kg/cm² Wire stoppers on side bulwark: 1 shipset Protection bar for the hatches on aft deck: 1 shipset

The Vessel specifications are reviewed and new brochures printed at regular intervals. Every endeavour has been made to provide accurate information on this brochure; however, the vessel owners do not accept any liability for errors, omissions or misprints published.